



SNA50FWM  
SNA100FWM  
SNA125FWM  
SNA140FWM  
SNA140FWM  
SNA160FWM



SNA71FHM  
SNA90FHM



MKW90A

**COMPATIBLE CON** Los equipos de conductos de la serie CITY-TECH de EKOKAI son compatibles con los sistemas de control inteligente de climatización de Airzone.



SUA50FAM



SUA71FAM



SUA90FAM



SUA100FAM  
SUA125FAM  
SUA140FAM  
SUA140FAT



SUA160FAT

MODELO		SNA50FWMX	SNA71FHMx	SNA90FHMx	SNA100FWMx	SNA125FWMx	SNA140FWMx	SNA140FWTx	SNA160FWTx
Potencia	Frio kW	5 (1.6 ~ 5.5)	7 (2.2 ~ 8.5)	8.5 (2.4 ~ 8.7)	10 (3.2 ~ 11.5)	12.1 (3.6 ~ 12.5)	13.4 (6 ~ 14.5)	13.4 (6 ~ 14.5)	16 (7.4 ~ 16.5)
	Calor kW	5.5 (1.4 ~ 6.8)	8 (2.4 ~ 9.5)	8.8 (2.4 ~ 9.9)	12 (2.9 ~ 14.5)	13.5 (3.9 ~ 15.5)	15.5 (5.2 ~ 17)	15.5 (5.2 ~ 17)	17 (6.2 ~ 18.5)
Eficiencia energética	SEER / SCOP	6.1 / 4	6.8 / 4	6.1 / 4	6.1 / 4	5.6 / 3.8	6.1 / 3.8	5.6 / 3.8	5.6 / 3.8
Clase energética	Frio / Calor	A+ / A+	A++ / A+	A++ / A+	A++ / A+	-	-	-	-
	Frio kW	1.5	1.94	2.58	3.2	4.1	4.4	4.7	5.4
Consumo eléctrico	Calor kW	1.4	2.11	2.38	3.4	4.1	4.6	4.4	5
	Frio A	6.3	8.5	11.8	13.9	17.9	19.9	7.2	7.7
Intensidad	Calor A	6	9.5	10.9	15.2	17	20.4	6.2	7.3
	V / f / Hz	220 ~ 240 / 1	220 ~ 240 / 1	220 ~ 240 / 1	220 ~ 240 / 1	220 ~ 240 / 1	220 ~ 240 / 1	380 ~ 415 / 3	380 ~ 415 / 3
Temperatura de trabajo	Frio °C	-20 ~ +48	-20 ~ +48	-20 ~ +48	-20 ~ +48	-20 ~ +48	-20 ~ +48	-20 ~ +48	-20 ~ +48
	Calor °C	-20 ~ +24	-20 ~ +24	-20 ~ +24	-20 ~ +24	-20 ~ +24	-20 ~ +24	-20 ~ +24	-20 ~ +24
Conexiones frigoríficas	Líquido Pul.	1/4	3/8	3/8	3/8	3/8	3/8	3/8	3/8
	Gas Pul.	1/2	5/8	5/8	5/8	5/8	5/8	5/8	5/8
Longitud máxima total / vertical	m	35 / 20	50 / 25	50 / 25	65 / 30	75 / 30	75 / 30	75 / 30	75 / 30
Cable de comunicación	n°x mm²	2 x 0,75	2 x 0,75	2 x 0,75	2 x 0,75	2 x 0,75	2 x 0,75	2 x 0,75	2 x 0,75
UNIDAD INTERIOR		SNA50FWM	SNA71FHM	SNA90FHM	SNA100FWM	SNA125FWM	SNA140FWM	SNA140FWM	SNA160FWM
Cable de alimentación	n°x mm²	3 x 1,5	3 x 1,5	3 x 1,5	3 x 1,5	3 x 2,5	3 x 2,5	3 x 2,5	3 x 2,5
Caudal de aire máx.	m³/h	950	1150	1500	1800	2000	2200	2200	2400
Presión estática	Rango	0 ~ 50	0 ~ 125	0 ~ 125	0 ~ 150	0 ~ 150	0 ~ 150	0 ~ 150	0 ~ 200
Presión sonora	dB(A)	36 ~ 42	36 ~ 39	38 ~ 40	40 ~ 44	37 ~ 40	38 ~ 41	38 ~ 41	38 ~ 41
Dimensiones Ancho / alto / fondo	mm	1000 / 200 / 450	900/260/655	900/260/655	1000 / 300 / 700	1400 / 300 / 700	1400 / 300 / 700	1400 / 300 / 700	1400 / 300 / 700
Embalaje Ancho / alto / fondo	mm	1308 / 275 / 568	1158/345/788	1158/345/788	1205 / 360 / 813	1601 / 365 / 813	1601 / 365 / 813	1601 / 365 / 813	1678 / 365 / 808
Peso neto / bruto	kg	26 / 31	31 / 39	31 / 39	41 / 47	50 / 56	50 / 56	50 / 56	57 / 64
UNIDAD EXTERIOR		SUA50FAM	SUA71FAM	SUA90FAM	SUA100FAM	SUA125FAM	SUA140FAM	SUA140FAT	SUA160FAT
Cable de alimentación	n°x mm²	3 x 2,5	3 x 4	3 x 4	3 x 4	3 x 6	3 x 6	5 x 2,5	5 x 2,5
Caudal de aire	m³/h	3000	3600	4000	5900	5900	5900	5900	6600
Presión sonora	dB(A)	53	52	53	55	55	56	57	57
Carga de refrigerante R32	kg	1	1.6	1.8	2.5	2.65	2.8	2.8	3.6
Longitud de precarga / carga adicional	m-g/m	7-16	7 - 25	7 - 30	7 - 35	7 - 35	9,5-40	9,5-40	9,5-40
Dimensiones Ancho / alto / fondo	mm	818 / 596 / 302	892 / 698 / 340	920 / 790 / 370	940 / 820 / 460	940 / 820 / 460	940 / 820 / 460	940 / 820 / 460	900 / 1345 / 340
Embalaje Ancho / alto / fondo	mm	948 / 645 / 420	1029 / 750 / 458	1083 / 855 / 488	1073 / 868 / 563	1073 / 868 / 563	1073 / 868 / 563	1073 / 868 / 563	1033 / 1395 / 443
Peso neto / bruto	kg	39 / 42	53 / 57	60 / 65	83 / 95	91 / 103	95 / 107	99 / 111	112 / 122
PVR	Unidad interior	541,63 €	581,00 €	740,25 €	890,75 €	1.146,88 €	1.154,13 €	1.154,13 €	1.365,88 €
	Unidad exterior	1.005,88 €	1.079,00 €	1.374,75 €	1.654,25 €	1.915,63 €	2.143,38 €	2.330,88 €	2.536,63 €
	Total	1.547,50 €	1.660,00 €	2.115,00 €	2.545,00 €	3.062,50 €	3.297,50 €	3.485,00 €	3.902,50 €
Accesorios: Wifi2: adaptador Wifi para control Smartphone.		70,00 €							
ONOF2: puerto on/off para tarjetero.		40,00 €							