



MSR30A



SUA50FAM



SUA71FAM



SUA90FAM



SUA100FAM  
SUA125FAM  
SUA140FAM  
SUA140FAT



SUA160FAT

MODELO		STA50FRMX	STA71FRMX	STA90FRMX	STA100FRMX	STA125FRMX	STA140FRMX	STA140FRTX	STA160FRTX
Potencia	Frío kW	5 (1.6 ~ 5.5)	7 (2.2 ~ 8.5)	8.5 (2.4 ~ 8.7)	10 (3.2 ~ 11.5)	12.1 (3.6 ~ 12.5)	13.4 (6.0 ~ 14.5)	13.4 (6.0 ~ 14.5)	16.0 (7.4 ~ 16.5)
	Calor kW	5.5 (1.4 ~ 6.8)	8 (2.4 ~ 9.5)	8.8 (2.4 ~ 9.9)	12 (2.9 ~ 14.5)	13.5 (3.9 ~ 15.5)	15.5 (5.2 ~ 17.0)	15.5 (5.2 ~ 17.0)	17 (6.2 ~ 18.5)
Eficiencia energética	SEER / SCOP	6.1 / 4	6.8 / 3.9	6.1 / 4	6.1 / 4	6.1 / 4	6.1 / 3.8	6.1 / 4.0	6.1 / 4
Clase energética	Frío / Calor	A++ / A+	A++ / A+	A++ / A+	A++ / A+	-	-	-	-
Consumo eléctrico	Frío kW	1.5	1.9	2.8	3.3	3.9	4.4	4.3	5.4
	Calor kW	1.6	2.4	2.6	3.6	3.9	4.3	4.4	5.4
Intensidad	Frío A	6.5	8.6	12.7	14.5	15.7	19.5	6.6	7.7
	Calor A	6.9	10.5	11.7	15.9	16.8	19.4	6.7	7.6
Tensión	V / f	220 ~ 240 / 1	220 ~ 240 / 1	220 ~ 240 / 1	220 ~ 240 / 1	220 ~ 240 / 1	220 ~ 240 / 1	380 ~ 415 / 3	380 ~ 415 / 3
Temperatura de trabajo	Frío °C	-20 ~ +48	-20 ~ +48	-20 ~ +48	-20 ~ +48	-20 ~ +48	-20 ~ +48	-20 ~ +48	-20 ~ +48
	Calor °C	-20 ~ +24	-20 ~ +24	-15 ~ +24	-20 ~ +24	-20 ~ +24	-20 ~ +24	-20 ~ +24	-20 ~ +24
Conexiones frigoríficas	Líquido Pul.	1/4.	3/8	3/8.	3/8	3/8	3/8	3/8	3/8
	Gas Pul.	1/2.	5/8	5/8.	5/8	5/8	5/8	5/8	5/8
Longitud máxima total / vertical	m	35 / 20	50 / 25	50 / 25	65 / 30	75 / 30	75 / 30	75 / 30	75 / 30
Cable de comunicación	n° x mm²	2 x 0,75	2 x 0,75	2 x 0,75	2 x 0,75	2 x 0,75	2 x 0,75	2 x 0,75	2 x 0,75
<b>UNIDAD INTERIOR</b>		<b>STA50FRM</b>	<b>STA71FRM</b>	<b>STA90FRM</b>	<b>STA100FRM</b>	<b>STA125FRM</b>	<b>STA140FRM</b>	<b>STA140FRM</b>	<b>STA160FRM</b>
Cable de alimentación	n° x mm²	3 x 1,5	3 x 1,5	3 x 1,5	3 x 1,5	3 x 1,5	3 x 1,5	3 x 1,5	3 x 1,5
Caudal de aire máx.	m³/h	850	1300	1500	1600	1800	2100	2100	2300
Presión sonora	dB(A)	36 ~ 44	38 ~ 45	39 ~ 49	43 ~ 49	42 ~ 49	44 ~ 52	44 ~ 52	45 ~ 54
Dimensiones Ancho / alto / fondo	mm	870 / 235 / 665	1200 / 235 / 665	1200 / 235 / 665	1200 / 235 / 665	1570 / 235 / 665	1570 / 235 / 665	1570 / 235 / 665	1570 / 235 / 665
Embalaje Ancho / alto / fondo	mm	1033 / 300 / 770	1363 / 300 / 770	1363 / 300 / 770	1363 / 300 / 770	1729 / 300 / 770	1729 / 300 / 770	1729 / 300 / 770	1729 / 300 / 770
Peso neto / bruto	kg	26 / 31	31 / 37	31 / 37	32 / 38	40 / 47	42 / 49	42 / 49	42 / 49
<b>UNIDAD EXTERIOR</b>		<b>SUA50FAM</b>	<b>SUA71FAM</b>	<b>SUA90FAM</b>	<b>SUA100FAM</b>	<b>SUA125FAM</b>	<b>SUA140FAM</b>	<b>SUA140FAT</b>	<b>SUA160FAT</b>
Cable de alimentación	n° x mm²	3 x 2,5	3 x 4	3 x 4	3 x 4	3 x 6	3 x 6	5 x 2,5	5 x 2,5
Caudal de aire	m³/h	3000	3600	4000	5900	5900	5900	5900	6600
Presión sonora	dB(A)	53	52	53	55	55	56	57	57
Carga de refrigerante R32	kg	1	1.6	1.8	2.5	2.6	2.8	2.8	3.6
Longitud precarga / carga adicional	m-g/m	7-16	7 - 25	7 - 30.	7 - 35	7 - 35	9,5-40	9,5-40	9,5-40
Dimensiones Ancho / alto / fondo	mm	818 / 596 / 302	892 / 698 / 340	920 / 790 / 370	940 / 820 / 460	940 / 820 / 460	940 / 820 / 460	940 / 820 / 460	900 / 1345 / 340
Embalaje Ancho / alto / fondo	mm	948 / 645 / 420	1029 / 750 / 458	1083 / 855 / 488	1073 / 868 / 563	1073 / 868 / 563	1073 / 868 / 563	1073 / 868 / 563	1033 / 1395 / 443
Peso neto / bruto	kg	39 / 42	53 / 57	60 / 65	83 / 95	91 / 103	95 / 107	99 / 111	112 / 122
<b>PVR</b>	<b>Unidad interior</b>	<b>634,13 €</b>	<b>968,50 €</b>	<b>1.067,75 €</b>	<b>1.248,25 €</b>	<b>1.304,38 €</b>	<b>1.374,13 €</b>	<b>1.374,13 €</b>	<b>1.608,38 €</b>
	<b>Unidad exterior</b>	<b>1.005,88 €</b>	<b>1.079,00 €</b>	<b>1.374,75 €</b>	<b>1.654,25 €</b>	<b>1.915,63 €</b>	<b>2.143,38 €</b>	<b>2.330,88 €</b>	<b>2.536,63 €</b>
	<b>Total</b>	<b>1.640,00 €</b>	<b>2.047,50 €</b>	<b>2.442,50 €</b>	<b>2.902,50 €</b>	<b>3.220,00 €</b>	<b>3.517,50 €</b>	<b>3.705,00 €</b>	<b>4.145,00 €</b>

Accesorios: Wifi2: adaptador Wifi para control Smartphone. **70,00 €**  
ONOF2: puerto on/off para tarjetero. **40,00 €**