

Combinaciones más comunes. Otras consultar.

MULTISPLIT 2 x 1 Modelo 2MA50JVE		MULTISPLIT 3 x 1 Modelo 3MA60JVE			MULTISPLIT 4 x 1 Modelo 4MA100JVE			
25+25	25+35	25+50	35+50	25+25+25	25+25+50	25+35+50	25+25+25+25	25+25+25+50
35+35		25+25+35	25+35+35	25+25+50	25+25+25+35	35+35+50	25+25+35+35	25+25+35+50

MULTISPLIT 5 x 1 Modelo 5MA125JVE							
35+35+35+35	35+35+35+50	25+25+25+25+25	25+25+25+25+35	25+25+25+25+50	25+25+25+25+71	25+25+25+35+35	25+25+25+35+50
35+35+35+71	35+35+50+50	25+25+25+50+50	25+25+35+35+35	25+25+35+35+50	25+35+35+35+35	25+35+35+35+50	35+35+35+35+35



Pueden combinarse indistintamente modelos de pared/cassette



MODELOS INTERIORES		DPA25JVI	DPA35JVI	DPA50JVI	DPA71JVI	DMA35JVI	DMA50JVI
Potencia	Frío kW	2.58 (1.40-3.30)	3.50 (1.70-3.70)	5.27 (2.50-5.80)	7.03 (2.90-7.30)	3.60 (1.70-3.70)	5.0 (2.50-5.6)
	Calor kW	2.70 (1.20-3.00)	3.50 (1.50-3.70)	5.37 (2.25-5.80)	7.05 (2.10-8.00)	3.9 (2.03-4.42)	5.6 (3.03-7.03)
Conexiones frigoríficas	Líquido Pul. / Gas Pul.	1/4 - 3/8	1/4 - 3/8	1/4 - 1/2	1/4 - 5/8	1/4 - 1/2	1/4 - 1/2
Caudal de aire Mín/Máx	m³/h	360 ~ 550	360 ~ 550	360 ~ 750	750 ~ 1150	530 ~ 700	530 ~ 700
Presión sonora	dB(A)	22~ 38	22 ~ 38	25 ~ 44	27~ 48	35 ~ 45	35 ~ 45
Dimensiones Ancho / alto / fondo	mm	750x285x200	750x285x200	900x310x225	1082x330x233	570x260x570	570x260x570
Embalaje Ancho / alto / fondo	mm	820x347x277	820x347x277	970x382x302	1155x397x312	655x295x655	655x295x655
Peso neto / bruto	kg	8 / 10.5	8.5 / 11	11 / 14	14 / 18	18 / 21	18 / 21
Dimensiones panel Ancho / alto / fondo	kg	-	-	-	-	650x650x55	650x650x55
Embalaje panel Ancho / alto / fondo	kg	-	-	-	-	710x710x80	710x710x80
Peso panel neto / bruto	kg	-	-	-	-	2.2 / 3.7	2.2 / 3.7

MODELOS EXTERIORES		2MA50JVE	3MA60JVE	4MA100JVE	5MA125JVE
Unidades interiores máx.		2	3	4	5
Potencia	Frío kW	5.3(2.0-5.8)	6.2(2.2-6.7)	10.50(2.5-11.0)	12(2.7-12.7)
	Calor kW	5.6(2.21-6.1)	6.6(2.39-7.26)	11.00(2.67-11.2)	13(2.9-13.1)
Eficiencia energética	SEER / SCOP	6.2 / 4	6.1 / 4	6.1 / 4.1	6.1 / 4
Clase energética	Frío / Calor	A++ / A+	A++ / A	A++ / A+	A++ / A+
Consumo eléctrico	Frío kW / Calor kW	1.7 / 1.5	1.9 / 1.7	3.9 / 3.1	4.4 / 3.7
Intensidad	Frío A / Calor A	7.6 / 6.5	8.3 / 7.8	17.5 / 13.9	19.7 / 16.2
Tensión	V / f	220 ~ 240 / 1	220 ~ 240 / 1	220 ~ 240 / 1	220 ~ 240 / 1
Rango de temperatura exterior	Frío °C	-10 ~ +52	-10 ~ +52	-10 ~ +52	-10 ~ +52
	Calor °C	-15~ +24	-15~ +24	-15~ +24	-15~ +24
Conexiones frigoríficas	Líquido Pul. / Gas Pul.	2 x 1/4 / 2 x 3/8	3 x 1/4 / 3 x 3/8	4 x 1/4 / 4 x 3/8	5 x 1/4 / 5 x 3/8
Longitud máxima unidad Ext. - Int.	m	25	30	35	35
Longitud máxima total instalación	m	40	60	80	80
Longitud vertical máxima Ext. - Int.	m	15	15	15	15
Longitud vertical máxima Int. - Int.	m	10	10	10	10
Cable de comunicación	n°x mm²	3 x 1,5 + T	3 x 1,5 + T	3 x 1,5 + T	3 x 1,5 + T
Cable de alimentación	n°x mm²	2 x 2,5 + T	2 x 4 + T	2 x 4 + T	2 x 6 + T
Compresor		DC Inverter	DC Inverter	DC Inverter	DC Inverter
Caudal de aire	m³/h	2300	3100	4000	4200
Presión sonora	dB(A)	55	56	61	61
Carga refrigerante R32	kg	1,05	1,25	2,3	2,3
Longitud precarga / carga adicional	m-g/m	15- 25	22.5- 25	30- 25	37.5 - 25
Dimensiones Ancho / alto / fondo	mm	800x545x315	834x655x328	985x808x395	985x808x395
Embalaje Ancho / alto / fondo	mm	920x620x400	945x725x435	1105x895x495	1105x895x495
Peso neto / bruto	kg	35 / 38	44 / 47	74 / 78	75 / 79

Accesorios: Wifi J1: Split Mural adaptador Wifi para control Smartphone / Wifi J2: Cassette adaptador Wifi para control Smartphone.