

# ESPECIFICACIONES

MODELO		<b>BNA200</b>	<b>BNA250</b>	<b>BNA300</b>	<b>BNA400</b>
		FWX	FWX	KWX-W	KWX-W
Potencia	Frío   kW	20	25	30	40
	Calor   kW	22	28.5	33	43
Eficiencia energética	SEER   SCOP	5.6   3.4	5   3	4.63   3.33	4.53   3.53
	EER   COP	2.75   3.25	2.69   3.31	2.65   3.2	2.6   3.1
Consumo eléctrico	Frío   kW	7.8	9.4	11.3	15.4
	Calor   kW	7.0	8.9	10.3	13.8
Intensidad	Frío   A	16	18.9	22.7	27.8
	Calor   A	15	17.2	20.7	26.4
Tensión	V / f	380 ~ 415 / 3	380 ~ 415 / 3	380 ~ 415 / 3	380 ~ 415 / 3
Temperatura de trabajo	Frío   °C	-7 ~ +48	-7 ~ +48	-7 ~ +48	-7 ~ +48
	Calor   °C	-15 ~ +24	-15 ~ +24	-15 ~ +24	-15 ~ +24
Conexiones frigoríficas	Líquido   Pul.	3/8	3/8	1/2	2 × 3/8
	Gas   Pul.	5/8	7/8	1	2 × 3/4
Long. máx. total   Vert. máx.	m	50   30	70   30	70   30	70   30
Cable de comunicación	n° × m	2 × 0.75	2 × 0.75	2 × 0.75	2 × 0.75
Número de unidades exteriores		1	1	1	2
UNIDAD INTERIOR		<b>BNA200</b>	<b>BNA250</b>	<b>BNA300</b>	<b>BNA400</b>
		FWI-W	FWI-W	KWI-W	KWI-W
Cable de alimentación	n° × m	3 × 1.5	3 × 1.5	3 × 2.5	5 × 2.5
Caudal de aire máx.	m³/h	3700	4200	5200	7000
Presión estática	Pa	120	120	120	120
	Rango	0 ~ 250	0 ~ 250	0 ~ 250	0 ~ 250
Presión sonora (min   med   max)	dB(A)	54	51   52   55	53   54   55	54   55   56
Dimensiones	Ancho   mm	1350	1520	1520	1680
	Alto   mm	360	450	450	650
	Fondo   mm	720	840	840	900
Embalaje	Ancho   mm	1565	1788	1788	1923
	Alto   mm	433	465	465	850
	Fondo   mm	861	988	988	1153
Peso	Neto   kg	65	103	105	175
	Bruto   kg	76	135	140	210



UNIDAD EXTERIOR		<b>BNA200</b> FWE <b>NUEVO</b>	<b>BNA250</b> FWE <b>NUEVO</b>	<b>BNA300</b> KWE	<b>2×BNA200</b> KWE
Cable de alimentación	n° x m	5 x 2.5	5 x 2.5	5 x 4	2 x (5 x 2.5)
Caudal de aire	m³/h	8400	11500	11000	2 x 8400
Presión sonora	dB(A)	61	63	65	62
Compresor Inverter Scroll	Marca	Mitsubishi Electric	Mitsubishi Electric	Hitachi	Mitsubishi Electric
Precarga de refrigerante	kg	3.8	6.2	9.5	2 x 6.4
(7.5 mts) R410 / adicional	g/m	—	—	120	2 x 60
(7.5 mts) <b>R32</b> / adicional	g/m	40	40	—	—
Dimensiones	Ancho   mm	900	940	940	2 x 940
	Alto   mm	1260	1615	1615	2 x 1430
	Fondo   mm	340	460	460	2 x 320
Embalaje	Ancho   mm	1033	1020	1020	2 x 1020
	Alto   mm	1405	1645	1645	2 x 1460
	Fondo   mm	443	560	560	2 x 420
Peso	Neto   kg	102	157	165	2 x 120
	Bruto   kg	110	162	182	2 x 130

**Accesorios:** ON/OFF 2FG: puerto on/off para tarjetero | Mandos Opcionales: MKW96P Programable · MKW97A Por cable (solo serie FW R-32)